## 15 - 25 H.P. Models



# K Series Two-Stage Air Compressors

#### STANDARD FEATURES

#### KC25 Unit Includes:

- √ Totally enclosed, OSHA type steel belt guard
- ✓ ASME/CRN air receiver
- √ Loadless starting
- ✓ Automatic start/stop
- √ ASME safety relief valves
- √ High efficiency industrial NEMA motor
- √ Discharge air service valve

#### **OPTIONS AVAILABLE**

- √ Low-oil level switch
- ✓ Electronic Tank Drain
- √ Magnetic Starters
- √ Vibration pads
- Alternate tank sizes





KC25-120H

K Series units are assembled in Canada, in our own factory, using the best quality components available in North America. Therefore, we can provide the highest quality & the most cost effective cast iron Two-Stage Compressor in the market.

K Series Air compressors come in vertical or horizontal tank mounted units with 5 - 25 H.P. motors. Our models provide capacity levels between 20 and 93 acfm @ 100 psig. The K Series Two-Stage Air Compressor comes in both electric & gas engine models.

We stand behind the workmanship of our product with a One-Year Warranty covering all components including the pump, motor and tank on all K Series air compressors.

#### **SPECIFICATIONS**

SPECS	HORIZONTAL TANKS					
UNIT MODEL	KC15-120H	KC15-240H	KC20-120H	KC20-240H	KC25-120H	KC25-240H
MOTOR H.P.	15	15	20	20	25	25
TANK SIZE	120 gallon	240 gallon	120 gallon	240 gallon	120 gallon	240 gallon
ACFM @100 psig (175 psig max.)	62	62	82	82	93	93
APPROX. WT. (lbs)	1800	2450	1800	2450	1800	2450
DIMENSIONS (LxWxH)	69 x 31 x 60	86 x 34 x 68	69 x 31 x 60	86 x 34 x 68	69 x 31 x 60	86 x 34 x 68

### **KC25 Pump Includes:**

- √ Cast iron cylinders, heads and crankcase for long, dependable compressor life
- √ Ring Flo lubrication
- √ Swedish steel concentric type inlet and discharge valves for low maintenance & high efficiency
- √ High efficiency inter cooler with steel fins on copper tubes designed for maximum heat dissipation
- √ Cast iron connecting rods with replaceable automotive type insert bearings
- √ Oil sight gauge
- √ High volume, statically balanced flywheel/cooling fan for improved cooling air flow
- √ Cast iron crankshaft supported on both ends by oversized tapered roller bearings
- √ Head unloaders
- √ Centrifugal unloader
- √ Combination filter silencer

#### Compressed Air International Inc.

Toll Free: 1-888-826-7247 Email: info@ca-intl.com Web Site: www.ca-intl.com

Vaughan Location: 60 Haist Ave. U # 1, Woodbridge, Ont. L4L 5V4 Phone: (905) 850-9888 Phone: (519) 837-0450 Fax: (905) 850-5676 Fax: (519) 837-0453

**Guelph Location:** 5477 RR#5 Hwy 6 North,



**K-Lub 4X Compressor Lubricant** Specially designed for your K Series Reciprocating Compressor

Distributed by:							